

HIGH PRODUCTIVITY

Powerful dual feed wheels mounted in Bandit's proven Slide Box Feed System provide direct down pressure to material entering the chipper, requiring little-to-no trim work on material before feeding it through the chipper.

Standard with a user-friendly radio remote control allowing the operator to control all track functions in addition to chipper feed forward / reverse, hydraulic lift cylinder up / down, discharge swivel / deflector and engine e-stop.



A Track One rubber track undercarriage is standard and provides high durability and flotation for traveling over a variety of terrain settings.

Weighing approximately 8,500 pounds and with a compact design the 12XP track can easily be maneuvered and transported.



6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178









FIND US ONLINE | WWW.BANDITCHIPPERS.COM

Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments

SPECIFICATIONS

MEASUREMENTS	TRACK	
Length (tray open):	142"	361 cm
Width:	77"	196 cm
Height:	96"	246 cm
Weight:	8,500 lbs.	3,855 kg
Engines:	CAT 74 or CAT 120 Horsepower	
Fuel Tank:	50 gal.	189.3 L
Hydraulic Tank:	50 gal.	189.3 L

UNDERCARRIAGES

Track: Rubber track undercarriage (Track One)

Standard & Custom Colors Available

Choose from two standard colors, or select a custom color to match your fleet.





Bandit Yellow Green

DIMENSIONS

Capacity: 12" 30.48 cm

Opening: 14.25" high x 17" wide 36.2 cm x 43.2 cm wide

Drum: 24" dia. x 18.75" wide 61 cm dia. x 47.6 cm wide

RPM: Approximately 1,530 RPM

Discharge: Height-adjustable, 360° hydraulic swivel with 12"

(30.5 cm) adjustable chip deflector

Feed System: Slide box feed system with (2) 17" (43.2 cm) adjustable down pressure springs, (2) 7-1/2" diameter x 17" wide feed wheels (19.05 cm x 43.18 cm) powered by (2) 15 CID hydraulic motors

Frame: Mainframe is constructed of 3/16" x 2" x 4" rectangular tubing (0.48 x 5.1 x 10.2 cm)



COMMITTED TO QUALITY & PRODUCTIVITY

Since 1983, Bandit has manufactured equipment for a multitude of wood waste processing markets. The vision since the beginning, is to build quality, highly productive, easy to maintain equipment providing years of dependable service.

The commitment for quality, innovation and dedication is instilled in every employee and is one of the main reasons why Bandit became an Employee-Owned Company (ESOP) in 2018. These core values ensure each Bandit machine will leave the factory ready to exceed your expectations.



Intimidator™ 12XP Track Features

- Rope/Line Shear Device (standard)
 Provides an improved chance that rope or lines inadvertently entering the chipper may be cut
- Last Chance Cables (standard)
 Stops/reverses the feed wheel when pulled in case of an emergency
- Operator Safety Control Bar (standard)
 Wraps around 3 sides of the infeed chute & controls the direction of feed wheels
- Wood Pusher Paddle (standard)
 Used to feed small wood debris into the chipper
- Chipper Hood Pin w/Padlock (standard) Prevents unauthorized access to the disc or drum
- Chipper Hood Engine Disable Plug (standard)
 Prevents engine from being started without the hood pin in place

Bandit Offers a Complete Line of Tree Care Equipment: Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments